Application No. 10/510,942 Filing Date: October 8, 2004 Docket: 2780 (203-3093 PCT US)

Page 2 of 14

LISTING OF CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in this

application:

1. (Currently Amended) An instrument introducer for facilitating the insertion of a

surgical instrument into a cavity or a body opening of a patient, comprising:

a tubular body portion defining a lumen therethrough, the tubular body portion having a

proximal end and a distal end; and

a distal end portion secured to the distal end of the tubular body portion, the distal end

portion defining a pocket and including a distal end wall configured and adapted to facilitate

passage of a surgical instrument.

2. (Original) The instrument introducer according to claim 1, wherein the distal end

portion includes an annular side wall depending from an outer terminal edge thereof.

3. (Original) The instrument introducer according to claim 2, wherein the distal end

portion is made from an elastomeric material.

4. (Original) The instrument introducer according to claim 2, wherein the distal end wall

of the distal end portion includes an aperture formed therein.

5. (Original) The instrument introducer according to claim 4, wherein the aperture is

coaxially aligned with a central longitudinal axis of the tubular body portion.

Application No. 10/510,942 Filing Date: October 8, 2004

Docket: 2780 (203-3093 PCT US)

Page 3 of 14

6. (Original) The instrument introducer according to claim 4, wherein the distal end

portion is secured to the distal end of the tubular body portion such that the annular side wall at

least partially overlaps the distal end of the tubular body portion.

7. (Original) The instrument introducer according to claim 6, wherein the distal end

portion is secured to the distal end of the tubular body portion such that the annular side wall

completely overlaps the distal end of the tubular body portion.

8. (Original) The instrument introducer according to claim 4, wherein a proximal

terminal edge of the annular side wall of the distal end portion is secured to a distal terminal edge

of the distal end of the tubular body.

9. (Original) The instrument introducer according to claim 7, wherein the distal end

portion is secured to the distal end of the tubular body by at least one of fusing, overmolding,

gluing and bonding.

10. (Original) The instrument introducer according to claim 4, wherein the tubular body

portion is fabricated from polypropylene.

11. (Original) The instrument introducer according to claim 4, further including a flange

extending radially outward from the proximal end of the tubular body portion.

Application No. 10/510,942 Filing Date: October 8, 2004

Docket: 2780 (203-3093 PCT US)

Page 4 of 14

12. (Original) The instrument introducer according to claim 3, wherein the distal end

wall of the distal end portion is provided with a region of weakened strength.

13. (Original) The instrument introducer according to claim 12, wherein the region of

weakened strength includes at least one of score lines, perforations, webbing and reduced

thickness.

14. (Currently Amended) The instrument introducer according to claim 4, wherein the

distal end wall of the distal end portion is shaped to define a pocket the distal end portion has a

frustroconical profile including a concave annular side wall.

15. (Currently Amended) An instrument introducer for facilitating the insertion of a

surgical instrument into a cavity or a body of a patient, comprising:

a hollow elongate cylindrical body including a distal end portion terminating in a distal

edge and a proximal end portion, the cylindrical body defining a central longitudinal axis; and

an elastomeric cap secured to the distal end portion of the cylindrical body, the cap

defining a pocket and including a distal end wall having an outer terminal edge and an annular

side wall depending from the outer terminal edge thereof, the distal end wall including an

aperture formed therein in the pocket, wherein a center of the aperture is coaxially aligned with

the central longitudinal axis.

Application No. 10/510,942 Filing Date: October 8, 2004

Docket: 2780 (203-3093 PCT US)

Page 5 of 14

16. (Original) The instrument introducer according to claim 15, wherein the cylindrical

body is configured and adapted to receive a surgical instrument therethrough.

17. (Original) The instrument introducer according to claim 15, further including a

flange extending radially outward from a proximal terminal edge of the proximal end portion of

the cylindrical body.

18. (Original) The instrument introducer according to claim 15, wherein the cap is

secured to the distal end of the cylindrical body such that the distal end wall of the cap is spaced

a distance from the distal terminal edge of the cylindrical body.

19. (Original) The instrument introducer according to claim 15, wherein the cap is

secured to the distal end of the cylindrical body such that a proximal terminal edge of the annular

side wall is secured to the distal terminal edge of the cylindrical body.

20. (Currently Amended) The instrument introducer according to claim 15, wherein the

distal end wall of the cap is shaped to define a pocket and wherein the aperture is formed in the

pocket the distal end portion has a frustroconical profile including a concave annular side wall.

21. (Currently Amended) A method of introducing a surgical instrument into a cavity or

a body opening of a patient, comprising the steps of:

Application No. 10/510,942 Filing Date: October 8, 2004

Docket: 2780 (203-3093 PCT US)

Page 6 of 14

providing an instrument introducer, wherein the instrument introducer includes a hollow

tubular body having a distal end portion and a proximal end portion defining a lumen

therebetween, and a resilient cap secured to the distal end of the tubular body, the cap defining a

pocket and including a distal end wall having an aperture formed therein;

inserting the distal end of the instrument introducer into the cavity or body opening of the

patient;

inserting a surgical instrument into the lumen of the tubular body of the instrument

introducer through a proximal end of the tubular body; and

advancing the surgical instrument through the lumen of the tubular body of the

instrument introducer until a distal end of the surgical instrument projects out through the

aperture of the cap, wherein the cap creates a seal around the perimeter of the surgical instrument

extending therefrom.

22. (Currently Amended) A method of introducing a surgical instrument into a cavity or

a body opening of a patient, comprising the steps of:

providing an instrument introducer, wherein the instrument introducer includes a hollow

tubular body having a distal end portion and a proximal end portion defining a lumen

therebetween, and a resilient cap secured to the distal end of the tubular body, the cap defining a

pocket and including a distal end wall having an aperture formed therein;

inserting a distal end of a surgical instrument into a proximal end of the tubular body of

the instrument introducer;

Filing Date: October 8, 2004

Application No. 10/510,942 Docket: 2780 (203-3093 PCT US)

Page 7 of 14

inserting the distal end of the surgical instrument, having the instrument introducer

placed thereon, into the cavity or body opening of the patient;

advancing the surgical instrument through the instrument introducer until the distal end of

the surgical instrument projects out through the aperture of the cap, wherein the cap creates a

seal around the perimeter of the surgical instrument extending therefrom.

23. (Currently Amended) An instrument introducer for facilitating the insertion of a

surgical instrument into a cavity or a body opening of a patient, comprising:

a tubular body portion defining a lumen therethrough, the tubular body portion having a

proximal end and a distal end;

a distal end portion secured to the distal end of the tubular body portion, the distal end

portion defining a pocket including a distal end wall configured and adapted to facilitate passage

of a surgical instrument therethrough, the distal end portion further including an annular side

wall depending from an outer terminal edge thereof;

wherein the distal end wall of the distal end portion includes an aperture formed therein.

and further wherein the aperture has a smaller diameter than a diameter of the end wall, and

wherein the aperture is provided with a region of weakened strength.